



A-Series[™] with Display

FASTER, EASIER ATM LOCK

Sargent and Greenleaf's globally trusted A-Series with Display incorporates a 30-character display with intuitive text, icons, and images for more efficient operation regardless of technician experience levels. A-Series with Display's enhanced USB audit features and optional time-saving one-time code app further simplify and streamline ATM service.

FEATURES

- EXTRA-LARGE VISUAL DISPLAY. An easy-to-use display improves speed and accuracy with up to 30 characters of text, icons, and images.
- QUICK ONE-TIME CODE GENERATION. Our optional A-Series OTC mobile app delivers one-time codes without time-consuming dispatch calls.
- **INTUITIVE OPERATION.** Display provides more information, making the lock easier to learn and use.
- DOWNLOAD MULTIPLE AUDIT TRAILS. USB download quickly captures up to 1,000 audit events from multiple locks. View, print, or email audit information without mailing keys.

Learn more at www.sargentandgreenleaf.com.

Protecting assets from high-security government sites to banks to businesses for more than 150 years, Sargent and Greenleaf continues to set the standard for innovation, security, quality, and trust.

Model 3006/3007/3028/3029

INTUITIVE ATM SECURITY WITH EXTRA-LARGE DISPLAY.

Integrated audio, visual, and text displays make A-Series with Display a fast, accurate way to protect your ATM network.

MODEL 3006 PIVOTBOLT

- Automatically re-locks to secure the safe whenever the container's boltwork moves to the fully closed position
- Lock bolt retraction and extension is controlled by the movement of the safe's boltwork
- Withstands 225 lbs. of bolt end pressure for a high level of security in boltwork blocking applications
- Stainless steel lock bolt





MODEL 3007 DIRECT DRIVE

- Lock bolt retraction and extension is controlled by turning of the keypad ring, offering dependable manual control of the locking bolt
- No-twist cable design prevents cable damage during opening
- Withstands 225 lbs. of bolt end pressure for a high level of security

MODEL 3028 DEAD LATCHING

- Motor-driven
- Withstands 225 lbs. of bolt end pressure for high security and durability in boltwork blocking applications
- Does not require direct attachment of the lock bolt to the safe's boltwork

MODEL 3029 PUSH/PULL

- Motor-driven
- Designed for direct boltwork attachment
- Push/pull strength of 2.4 lbs. with maximum load of 5.6 lbs.
- Bolt has drilled and tapped holes



For more information, to find part numbers, or to place an order, visit us online or contact your Sargent and Greenleaf sales representative.

www.sargentandgreenleaf.com/aserieswithdisplay

SPECIFICATIONS

CERTIFICATIONS

- UL Type 1
- VdS Class 2
- CEN B*
- A2P B/E*
- RoHS Compliant**Pending

MODES OF OPERATION

- Bank Mode: no key required; up to 30 users
- Service Mode: PIN, touch key, and one-time code available immediately via app required to open
- Bank + Service Mode: users from either category can access the lock without changing programming

INSTALLATION

- Standard S&G Magic Module footprint
- Universally handed: left hand, right hand, up, or down mounting
- No vendor meets
- 10-minute average installation time

OPERATION

- Secure loop for connection to other security system components
- Bolt position indicator closes a circuit when lock bolt is in locked or unlocked position
- One-hand operation key snaps in to iButton
- Interface includes beeps and braps, indicator lights, and 30-character display with icons, images, and text
- Multi-language software with optional custom translator
- Penalty lockout after five failed attempts
- Time delay up to 99 minutes
- Immediate power up via two 9V alkaline batteries
- Low battery signal

ADDITIONAL OPTIONS

- One-time code app for mobile device
- A-seal generator
- Audit trail software for fast, precise management of audit data

WARRANTY

Two-year limited warranty

